

REFERENCE NO.	PLAN & PROFILE SHEET NO.	STATION		SIDE	STORM																			604		
					602				603											604						
					CONCRETE MASONRY				525 mm CONDUIT, TYPE B, AS PER PLAN	900 mm CONDUIT, TYPE B, AS PER PLAN (62.5 D-LOAD)	900 mm CONDUIT, TYPE C, AS PER PLAN (62.5 D-LOAD)	900 mm CONDUIT, TYPE C, AS PER PLAN (75 D-LOAD)	900 mm CONDUIT, TYPE C, BORED OR JACKED, AS PER PLAN (150 D-LOAD)	1050 mm CONDUIT TYPE B, AS PER PLAN (87.5 D-LOAD)	1050 mm CONDUIT TYPE C, AS PER PLAN (87.5 D-LOAD)	1200 mm CONDUIT, TYPE B, AS PER PLAN (62.5 D-LOAD)	1200 mm CONDUIT, TYPE B, AS PER PLAN (75 D-LOAD)	1200 mm CONDUIT TYPE B, BORED OR JACKED, AS PER PLAN (150 D-LOAD)	1200 mm CONDUIT, TYPE C, AS PER PLAN (62.5 D-LOAD)	1500 mm CONDUIT, TYPE C, AS PER PLAN (87.5 D-LOAD)					MANHOLE NO. 3 AS PER PLAN: TYPE B	MANHOLE NO. 3 AS PER PLAN
CU.METER				METER	METER	METER	METER	METER	METER	METER	METER	METER	METER	METER	METER	METER					EACH	EACH	EACH			
D1	97	5+400	0+072.5	☐																						
D2		0+072.5	0+096.5	☐										24	36	16.5										
D3		0+096.5	0+140	☐													40									
D1	98	0+140	0+173.98	☐																						
D2		0+173.98		☐	1.07																					
D1	101	4+443.7		L																						
D2		4+443.7	4+438.5	L										7.3												
D3		4+438.5		L&☐																						
D4		4+438.5		☐&R		2.4	14.3																			
D5		4+438.5	4+452	R				19.2																		
D6		4+452	4+460	R					8																	
D1	102	4+460	4+470	R						5.1																
D2		4+470	4+577	R							120.3															
D3		4+577	4+600								14.5															
D1	103	4+600	4+740	R																						
D1	104	4+740	4+801.5	R																						
TOTALS CARRIED TO 58A SUMMARY					1.07			2.4	14.3	221.8	27.6	120.3	30.7	7.3	24	36	16.5	75	4.8					2	6	1

ESTIMATED QUANTITIES
 OUTLET CHANNEL AND RELIEF SEWER
 LAK-640-2.14
 105/214