

mitigation, unless the District Engineer determines that activity-specific compensatory mitigation is more appropriate, based on which is best for the aquatic environment. These types of mitigation are preferred because they involve larger blocks of protected aquatic environment, are more likely to meet the mitigation goals, and are more easily checked for compliance. If a mitigation bank or other consolidated mitigation approach is not available in the watershed, the District Engineer will consider other appropriate forms of compensatory mitigation to offset the losses of waters of the United States to ensure that the net adverse effects of the authorized work on the aquatic environment are minimal.

20. Spawning Areas. Activities, including structures and work in navigable waters of the United States or discharges of dredged or fill material, in spawning areas during spawning seasons must be avoided to the maximum extent practicable. Activities that result in the physical destruction (e.g., excavate, fill, or smother downstream by substantial turbidity) of an important spawning area are not authorized.

21. Management of Water Flows. To the maximum extent practicable, the activity must be designed to maintain preconstruction downstream flow conditions (e.g., location, capacity, and flow rates). Furthermore, the activity must not permanently restrict or impede the passage of normal or expected high flows (unless the primary purpose of the fill is to impound waters) and the structure or discharge of dredged or fill material must withstand expected high flows. The activity must, to the maximum extent practicable, provide for retaining excess flows from the site, provide for maintaining surface flow rates from the site similar to preconstruction conditions, and must not increase water flows from the project site, relocate water, or redirect water flow beyond preconstruction conditions. In addition, the activity must, to the maximum extent practicable, reduce adverse effects such as flooding or erosion downstream and upstream of the project site, unless the activity is part of a larger system designed to manage water flows.

22. Adverse Effects From Impoundments. If the activity, including structures and work in navigable waters of the United States or discharge of dredged or fill material, creates an impoundment of water, adverse effects on the aquatic system caused by the accelerated passage of water and/or the restriction of its flow shall be minimized to the maximum extent practicable.

23. Waterfowl Breeding Areas. Activities, including structures and work in navigable waters of the United States or discharges of dredged or fill material, into breeding areas for migratory waterfowl must be avoided to the maximum extent practicable.

24. Removal of Temporary Fills. Any temporary fills must be removed in their entirety and the affected areas returned to their preexisting elevation.

25. Designated Critical Resource Waters. Critical resource waters include, NOAA-designated marine sanctuaries, National Estuarine Research Reserves, National Wild and Scenic Rivers, critical habitat for Federally listed threatened and endangered species, coral reefs, State natural heritage sites, and outstanding national resource waters or other waters officially designated by a State as having particular environmental or ecological significance and identified by the District Engineer after notice and opportunity for public comment. The District Engineer may also designate additional critical

resource waters after notice and opportunity for comment.

(a) Except as noted below, discharges of dredged or fill material into waters of the United States are not authorized by NWP's 7, 12, 14, 16, 17, 21, 29, 31, 35, 39, 40, 42, 43, and 44 for any activity within, or directly affecting, critical resource waters, including wetlands adjacent to such waters. Discharges of dredged or fill materials into waters of the United States may be authorized by the above NWP's in National Wild and Scenic Rivers if the activity complies with General Condition 7. Further, such discharges may be authorized in designated critical habitat for Federally listed threatened or endangered species if the activity complies with General Condition 11 and the U.S. Fish and Wildlife Service or the National Marine Fisheries Service has concurred in a determination of compliance with this condition.

(b) For NWP's 3, 8, 10, 13, 15, 18, 19, 22, 23, 25, 27, 28, 30, 33, 34, 36, 37, and 38, notification is required in accordance with General Condition 13, for any activity proposed in the designated critical resource waters including wetlands adjacent to those waters. The District Engineer may authorize activities under these NWP's only after he determines that the impacts to the critical resource waters will be no more than minimal.

26. Fills Within 100-Year Floodplains. For purposes of this general condition, 100-year floodplains will be identified through the Federal Emergency Management Agency's (FEMA) Flood Insurance Rate Maps or FEMA-approved local floodplain maps.

(a) Discharges Below Headwaters. Discharges of dredged or fill material into waters of the United States resulting in permanent, above-grade fills within the 100-year floodplain at or below the point on a stream where the average annual flow is five cubic feet per second (i.e., below headwaters) are not authorized by NWP's 29, 39, 40, 42, 43, and 44. For NWP's 12 and 14, the prospective permittee must notify the District Engineer in accordance with General Condition 13 and the notification must include documentation that any permanent, above-grade fills in waters of the United States within the 100-year floodplain below headwaters comply with FEMA or FEMA-approved local floodplain construction requirements.

(b) Discharges in Headwaters (i.e., above the point on a stream where the average annual flow is five cubic feet per second).

(1) Flood Fringe. Discharges of dredged or fill material into waters of the United States resulting in permanent, above-grade fills within the flood fringe of the 100-year floodplain of headwaters are not authorized by NWP's 12, 14, 29, 39, 40, 42, 43, and 44, unless the prospective permittee notifies the District Engineer in accordance with General Condition 13. The notification must include documentation that such discharges comply with FEMA or FEMA-approved local floodplain construction requirements.

(2) Floodway. Discharges of dredged or fill material into waters of the United States resulting in permanent, above-grade fills within the floodway of the 100-year floodplain of headwaters are not authorized by NWP's 29, 39, 40, 42, 43, and 44. For NWP's 12 and 14, the permittee must notify the District Engineer in accordance with General Condition 13 and the notification must include documentation that any permanent, above-grade fills proposed in the floodway comply with FEMA or FEMA approved local floodplain construction requirements.