



EXTRA AREA - COUNTRY CLUB DRIVE
 94 Sq.Yds. 1" Asph. conc. surface course T-35
 94 Sq.Yds. 1/2" Asph. conc. leveling course B-35
 94 Sq.Yds. 8" Portland cement conc. base B-70
 100 Sq.Yds. 4" Subbase Grade "D"
 94 Sq.Yds. Bituminous tack coat T-30
 42 Cu.Yds. Excavation E-1

EXTRA AREA - RUSH ROAD
 139 Sq.Yds. 1" Asph. conc. surface course T-35
 139 Sq.Yds. 1/2" Asph. conc. leveling course B-35
 139 Sq.Yds. 8" Portland cement conc. base B-70
 145 Sq.Yds. 4" Subbase Grade "D"
 139 Sq.Yds. Bituminous tack coat T-30
 60 Cu.Yds. Excavation E-1

EXTRA AREA - RIDGEHURST RD.
 81 Sq.Yds. 1" Asph. conc. surface course T-35
 81 Sq.Yds. 1/2" Asph. conc. leveling course B-35
 81 Sq.Yds. 8" Portland cement conc. base B-70
 89 Sq.Yds. 4" Subbase Grade "D" or "C"
 81 Sq.Yds. Bituminous tack Coat T-30
 37 Cu.Yds. Excavation E-1

EXTRA AREA - PINE RIDGE DR.
 86 Sq.Yds. 1" Asph. conc. surface course T-35
 86 Sq.Yds. 1/2" Asph. conc. leveling course B-35
 86 Sq.Yds. 8" Portland cement conc. base B-70
 94 Sq.Yds. 4" Subbase Grade "D" or "C"
 86 Sq.Yds. Bituminous tack coat T-30
 39 Cu.Yds. Excavation E-1

WATER
 Adjust Valve boxes to Grade 7 Each

For Construction Profile, see note on Sheet 2.

STORM SEWERS

Ref. No.	Station		Side Et. or Lt.	I-2 Lin. Ft. 12" Class "B"	I-3 Each		I-16 Each Abandon C.B.	Location of Structure
	From	To			Adjust To Grade M.H.C.B.	Std. C.B.		
1-S	130+95	131+11	L&R	18	1	1	1	131+95 131+00 131+11
2-S	138+09	138+61	L&R	1	2	1	1	138+09 138+60 138+61
TOTALS				18	1	4	1	

EXCAVATION	396	Cu.Yds.
EMBANKMENT	478	Cu.Yds.
EMB. + 22%	583	Cu.Yds.

ESTIMATED QUANTITIES

REF. NO.	STATION TO STATION	SIZE	T-35 For Drives	E-1 For Drives	E-1 For Encountered Drives	T-70 Conc. For Drives
1-A	132+85	R	2	2	2	2
2-A	133+46	L	2	2	2	2
3-A	133+74	R	2	2	2	2
4-A	134+11	R	2	2	2	2
5-A	135+46	R	2	2	2	2
6-A	136+38	R	2	2	2	2
7-A	136+72	R	2	2	2	2
8-A	137+22	L	2	2	2	2
9-A	137+25	R	2	2	2	2
10-A	138+13	R	2	2	2	2