

RESURFACING QUANTITIES

LAKE COUNTY
LAK-90/271-1.88/0.00

OHIO
FHWA REGION 5
FEDERAL PROJECT

15
49

PLOT SUBMITTED BY: GRMOVSEK

PLOT SUBMITTED: 4-MAY-1990 10:06

ZFI:\100,350\OLK90GBA.DGN

RESURFACING QUANTITIES							
LOCATION		SIDE	END WIDTHS LIN FT	254		446	
				PAVEMENT PLANING, BITUMINOUS	1 1/4" ASPHALT CONCRETE SURFACE COURSE, TYPE 1, AC-20, AS PER PLAN	SQ YDS	CU YDS
FROM	TO						
RAMP "A"							
29+21.53	25+46.12		40	1668.5	57.9		
25+46.12	24+27		36	476.5	16.5		
24+27	22+77		37	616.67	21.4		
22+77	8+22		38	6143.3	213.2		
8+22	6+21.71		40	890.0	30.9		
6+21.71	6+00		41	98.9	3.4		
RAMP "B"							
26+85.07	25+03		36	728.3	25.3		
25+03	23+53		37	616.7	21.4		
23+53	16+60.75		38	2922.8	101.4		
16+60.75	15+35.75		34	472.2	16.4		
9+41.75	8+16.75		34	472.2	16.4		
8+16.75	5+79.29		38	1002.6	34.8		
RAMP "C"							
42+28.41	40+97		40	584.0	20.3		
40+97	35+48.05		38	2317.8	80.4		
35+48.05	34+22.23		34	475.3	16.5		
32+79.49	31+54.93		34	470.6	16.3		
31+54.93	27+09		38	1882.8	65.3		
27+09	25+84		34	472.2	16.4		
19+97	18+72		34	472.2	16.4		
18+72	10+62		38	3420.0	118.7		
10+62	8+13.64		43	1186.6	41.2		
RAMP "D"							
38+78.80	37+54		40	554.7	19.2		
37+54	22+12		38	6510.7	226.0		
22+12	20+62		37	616.7	21.4		
20+62	18+13.64		36	993.4	34.5		
SUB-TOTAL COLUMN 1				36066	1252		

RESURFACING QUANTITIES							
LOCATION		SIDE	END WIDTHS LIN FT	254		446	
				PAVEMENT PLANING, BITUMINOUS	1 1/4" ASPHALT CONCRETE SURFACE COURSE, TYPE 1, AC-20, AS PER PLAN	SQ YDS	CU YDS
FROM	TO						
RAMP "E"							
4+63.97	7+56		25	811.9	28.2		
7+56	10+13.97		26	745.2	25.9		
10+13.97	20+71.96		27	3174.0	110.2		
S.R. 91 CONNECTION				24	288.1	10.0	
RAMP "F"							
4+74+39	7+10.29		35	917.4	31.8		
7+10.29	9+50		31	825.7	28.7		
9+50	20+17		27	3201.0	111.1		
20+17	22+16.66		29	643.3	22.3		
RAMP "G-H"							
5+23.01	6+53.13		62	983.2	34.1		
6+53.13	7+88.61		61	918.3	31.9		
7+88.61	10+49.98		57	1655.3	57.4		
10+49.98	13+69.70		54	1918.3	66.6		
RAMP "G"							
3+69.70	8+93.98		27	1572.8	54.6		
8+93.98	10+44		27	450.06	15.6		
10+44	11+43.98		29	322.2	11.2		
RAMP "H"							
13+69.70	22+99.60		27	2789.7	96.8		
22+99.60	23+50		26.5	148.4	5.1		
23+50	25+49.60		25	554.4	19.2		
25+49.60	28+49.60		26	866.67	30.1		
RAMP "J"							
4+53.04	6+03		26.5	441.5	15.3		
6+03	11+74.62		22	1397.3	48.5		
SUB-TOTAL COLUMN 2				24625	855		

RESURFACING QUANTITIES							
LOCATION		SIDE	END WIDTHS LIN FT	254		446	
				PAVEMENT PLANING, BITUMINOUS	1 1/4" ASPHALT CONCRETE SURFACE COURSE, TYPE 1, AC-20, AS PER PLAN	SQ YDS	CU YDS
FROM	TO						
RAMP "K"							
2+45.60	9+00		22	1599.6	55.5		
9+00	10+50		23.5	391.67	13.6		
10+50	13+50		25	833.3	28.9		
RAMP "L"							
5+45.58	10+45		24	1331.8	46.2		
10+45	11+95		26.5	441.67	15.3		
11+95	18+97.23		27	2106.7	73.1		
RAMP "M"							
8+37.55	13+62.48		27	1574.79	54.6		
13+62.48	16+12.48		28	777.78	27		
RAMP "N"							
6+12.41	7+10		29	314.5	10.9		
7+10	13+22.37		27	1837.1	63.7		
13+22.37	16+56.39		31	1150.5	39.9		
16+56.39	18+72.52		35	840.5	29.2		
RAMP "P"							
9+36.70	17+65.16		27	2485.4	86.2		
17+65.16	18+15		26.5	146.8	5.1		
18+15	20+15.16		27	600.5	20.8		
20+15.16	23+15.16		25	833.3	28.9		
RAMP "Q"							
3+96	4+96		26.5	294.4	10.2		
4+96	12+28.39		22	1790.3	62.1		
SUB-TOTAL COLUMN 3				19351	671		

RESURFACING QUANTITIES							
LOCATION		SIDE	END WIDTHS LIN FT	254		446	
				PAVEMENT PLANING, BITUMINOUS	1 1/4" ASPHALT CONCRETE SURFACE COURSE, TYPE 1, AC-20, AS PER PLAN	SQ YDS	CU YDS
FROM	TO						
RAMP "R"							
0+00	5+11.88		22	1251.3	43.4		
5+11.88	6+11.44		23.5	260	9		
6+11.44	6+61.44		23.5	130.6	4.5		
6+61.44	7+61.88		25.5	284.6	9.9		
7+61.88	10+61.95		25	833.5	28.9		
RAMP "S"							
0+00	3+00		25	833.3	28.9		
3+00	4+00		25.5	283.3	9.8		
4+00	4+50		25	138.9	4.8		
4+50	5+50		23.5	261.1	9.1		
5+50	11+27.51		22	1411.7	49		
RAMP "T"							
0+00	4+46.28		22	1090.9	37.9		
4+46.28	5+46.28		26.5	294.4	10.2		
SUB-TOTAL COLUMN 4				7074	246		
GRAND TOTAL-THIS SHEET				87116	3024		
PART 2							

ITEM 407 - TACK COAT			
PART 1			
64850	S.Y. X 0.10 GAL/S.Y. =	6485	GAL.
PART 2			
623079	S.Y. X 0.10 GAL/S.Y. =	62308	GAL.