

620 DELINEATORS

LAKE COUNTY
LAK-90-6.71

OHIO
FHWA
REGION 5

133
182

ROADWAY	STATION		SIDE	INTERVAL	TYPE C		TYPE D	
	FROM	TO			FLEX. POST	BRACK.	FLEX. POST	BRACK.
MAINLINE (EASTBOUND)								
3-EB	308+41	335+00	RT.	400	7			
	335+00	346+00	RT.	200	6			
	348+00	373+00	RT.	400	6			
	373+00	375+00	RT.	200	1			
	10+99.63	14+50	RT.	200	2			
	14+50	31+80	RT.	400	4			
	31+80	140+53.07	RT.	400	28			
2-EB	143+40.31	241+39.02	RT.	400	24			
	242+80.20	246+00	RT.	400	1			
	246+00	251+00	RT.	200	2			
	251+00	280+89	RT.	400	7			
MAINLINE (WESTBOUND)								
3-WB	308+41	340+00	LT.	400	8			
	340+00	345+50	LT.	200	3			
	349+50	366+00	LT.	400	4			
	366+00	363+20	LT.	200	1			
	363+20	375+00	LT.	200	4			
	10+99.63	14+00	LT.	200	2			
	14+00	89+00	LT.	400	19			
2-WB	89+00	140+53.07	LT.	400	13			
	143+40.31	239+00	LT.	400	24			
	239+00	246+00	LT.	200	4			
	246+00	264+00	LT.	400	5			
	264+00	270+00	LT.	200	3			
	270+00	280+89	LT.	400	3			
RAMP "L"								
	5+50	17+50	LT.	200	7			
	11+50	13+50	RT.	200		2		
RAMP "M"								
	9+00	13+00	LT.	200	3			
	13+00	15+00	RT.	200		2		
RAMP "N"								
	7+10	15+10	LT.	200			5	
	15+10	17+10	RT.	200	2			
RAMP "P"								
	11+00	15+00	RT.	200	3			
	15+00	17+00	LT.	200		2		
TOTAL					196		11	

T:\DGN\LAK-90\TRAFFCON\5774161.DGN

T:\DGN\LAK-90\TRAFFCON\5774161.DGN